




## 8-WAY FAN-OUT CABLE WITH WATERPROOF ADAPTOR

Features	OMPC 8x 025 LC OHR 57003899	OMPC 8x 15 LC OHR 57003898	OMPC 8x 025 LC/SC 57004036
			
Length	2,5 m	15 m	2,5 m
Connectors	8 x LC/APC	8 x LC/APC	8 x LC/APC / 8 x SC/APC
Fan-out pigtails		8 x G.675.A2, 0.9 mm colour coded	
Fan-out length	150 mm	150 mm	150 mm / 300 mm
Adaptor		waterproof 5/8" UNEF	
Jacket		black, diameter 5 mm	
Accessory		10161204 PG 11 – 5/8" reducing adaptor	



## OPTOPAD - OPTICAL MEASURING DEVICE

- Identification of the signal quality with the OMI App
- Applicable everywhere where CATV signals are transferred over fibreglass
- Simple application without further measuring devices
- Optical and USB interface available
- Level adjustment manually or automatically
- Recommendation of optimal OMI value
- Portable
- Item No. 57002337



Technical data		Optopad	Remarks
Optical input wavelength ( $\lambda$ )	nm	1260-1620	
Optical input power	dBm	min. -4 dBm max. 17 dBm	
Frequency range	MHz	15-1006	
Number of HF carriers		100 digital, 100 analogue	
OMI measuring range	Type 1	1 carrier 13%-50% 100 carriers 1.5%-5%	
	Type 2	1 carrier 5%-50% 100 carriers 0.1%-5%	
Operating temperature	°C	0...50	
Fibre optic connection		SC / APC	Patch cords for other connections
Battery life	hrs.	2	
USB-interface			
Fibre optic connection		SC / APC	
Dimensions	mm	116 x 72 x 24	
Storage temperature	°C	-20...60	